

4/8 CHANNELS DIGITAL SURVEILLANCE STANDALONE MJPEG



Advanced M-Jpeg Compression

Triplex: Simultaneous Live Display/ Playback, Record and Back-up

Multiple Recording Modes: Schedule, Event (Pre/Post), Manual,

Simultaneous Monitoring Via Composite, S-Video, VGA (Option)

USB1.1 Port for External Backup Device (Front)

Powerful Network Protocol : DHCP, Static IP, PPP

RS 485 for PTZ and Keypad

Hidden/Covert Camera

Specifications

MODEL	SCDVR-M0450	SCDVR-M0850
Video Input /Loop output	4/4 (NTSC/PAL)	8/8 (NTSC/PAL)
Video Output	1 Monitor, 1 spot out, 1 S-video, 1 VGA (Option)	
Storage Capacity	2 HDD	
Compression	ADVANCED M-JPEG	
Operation System	EMBEDDED LINUX	
Live Display Resolution	NTSC : 720x480; PAL : 720x576	
Recording Rate	NTSC : 720x240 (60fps); 360x240 (Quad : 120fps)	
	PAL : 720x288 (50fps); 360x288 (Quad : 100fps)	
Alarm In/Relay Out	4/1	8/1
System Control	Key Button, IR Remote, Remote Client	
Live Display Speed	NTSC : 120fps; PAL : 100fps	NTSC : 240fps; PAL : 200fps
Audio Record	1 channel	
Display	Brightness, Contrast, Color Adjustments per Channel	
Camera Title	8 Characters per Channel	
Recording Mode	Manual, Schedule, Alarm & Motion	
Search Mode	Date & Time, Camera, Alarm /Motion	
Playback Mode	Forward, Reverse, Pause, Frame by Frame, 2X, 4X, 8X, 16X	
System Utility	2 Level Password/AutoLock	
Back-Up	Ethernet, Remote PC, External Recording Devices, VCR	
External Recording Devices	Flash Memory Stick	
HDD	1 internal HDD, 1 Removable HDD (max 800GB)	
Network	LAN, WAN, Internet, PSTN Line	
Remote Client Software	Central Management Software	
Power Supply	AC100-230V, (50/60Hz) Free voltage	
Power Consumption	50W (220V); 40W (110V)	
Operating Temperature	0 deg ~ 40 deg	
Dimension /Weight	335(W) x 370(D) x 70(H) / 4 Kg	

Specifications are subject to change without notice